



## DESCRIPTION

THE FLEXIBLE LOOP IS USED TO CONVEY THE CO<sub>2</sub> FROM THE GAS OUTLET OF THE CYLINDER VALVE TO THE CHECK VALVE MANIFOLD ABOVE THE CYLINDERS.

WORKING PRESSURE	160 BAR
BURST PRESSURE	640 BAR
MIN BEND RADIUS	180mm

## MATERIAL

HIGH PRESSURE HOSE  
INTERNAL SPRING  
END NUT COUPLINGS

HOSE CONNECTORS  
TEST PRESSURE  
WEIGHT

DUNLOP DH85-8 PIN PRICKED COVER  
GALVANISED STEEL WIRE  
MILD STEEL PLATED.  
THREAD W21.8 x  $\frac{1}{4}$ " DIN 477  
MILD STEEL PLATED  
210 BAR (3045PSI)  
0.53Kg

Flexible Discharge Hose  
Part K97112  
Kidde CO<sub>2</sub> Systems

[sales@norrscope.com](mailto:sales@norrscope.com)

CPD 89/106/EEC

ALL DIMENSIONS IN mm's UNLESS OTHERWISE STATED

1	29.05.12	ORIGINAL ISSUE	
REV	DATE	REASON FOR ISSUE	APP