

## 3M<sup>™</sup> Scott<sup>™</sup> EPIC 3 Voice Amplifier



## **Description**

Effective communication is essential for first responders, who often face life-threatening scenarios.

Developed in response to the needs voiced by fire fighters and other emergency workers, the 3M™ Scott™ EPIC 3 Voice Amplifier offers first responders wearing respiratory protection equipment reliable, hands-free, person-to-person communications.

The EPIC 3 Voice Amplifier provides a dependable, easy-to-use means of voice communications with added features such as auto shut-off and directional speaker. When communication is critical, connect with 3M™ Scott™ EPIC communications products.

## **Specification**

| opoomounon                  |  |
|-----------------------------|--|
| Physical                    |  |
| Dimensions                  | 100mm x 60mm x 58mm  |
| Weight                      | 198g with 3 AAA batteries  |
|                             |  |
| Microphone                  |  |
| Туре                        | High sensitivity microphone with auto gain control and breath detection technology |
| Speaker                     |  |
| Туре                        | Custom 40mm speaker  |
| Frequency response          | 300-4000Hz   |
| Communications              |  |
| Facepiece voice enhancement | Amplifies and enhances facepiece voice intelligibility                             |
| Part numbers                |  |
| 2031843                     | EPIC 3 Voice Amp AV-3000HT (open bracket)  |
| 2031844                     | EPIC 3 Voice Amp Vision3   |
| 2031845                     | EPIC 3 Voice Amp Promask   |
| Speaker                     |  |
| Туре                        | Custom 40mm speaker  |
| Frequency response          | 300-4000Hz   |

| Power                                   |  |
|---|--|
| Source                                  | 3 – AAA Alkaline batteries, intrinsically safe; compatible with rechargeable NiMH batteries  |
| Battery life                            | Designed to deliver 50 hours runtime with AAA Alkaline batteries @ 25% voice amplification duty cycle use  |
|   |  |
| Environmental                           |  |
| High heat and flame                     | 500°F/260°C for 5 min soak with a 10 second flame followed by a 6 inch drop  |
| Standard heat and flame                 | 203°F/95°C for 15 minute soak with a 10 second flame followed by a 6 inch drop   |
| Radiant heat                            | 15 kW/m² for 5 minutes at 7 inches +/- 1 inch from heat source followed by a 6 inch drop   |
| Storage temp                            | -30°C to +60°C   |
| Humidity                                | MIL-STD 507.x PROC. II   |
| Ingress protection                      | IP66 and IP67  |
| Drop and tumble                         | 6ft drop all 6 sides – 30 minute tumble  |
| Regulatory approvals and certifications |  |
| NFPA                                    | NFPA 1981 approved (2002/2007/2013 Editions). Complies with NFPA 2013 Edition SCBA Sound Transmission Index (STI) acoustic standards for voice intelligibility                                   |
| NIOSH                                   | Meets NIOSH 42 CFR, Part 84 certification standard   |
| ESD                                     | IEC/EN 61000-4-2   |
| Intrinsic Safety Rating                 | UL 913, IS 6th and 7th Editions: Class I, II, III, Division 1, Groups C, D, E, F and G. Ex ia IIB T3 Ga IP66/67; IEC standards IEC 60079-0: 2007-10 Edition 5; and IEC 60079-11:2011 Edition 6.0 |