

MODEL FL4000H INTELLIGENT MULTI-SPECTRAL FLAME DETECTION SYSTEM



FL4000H - 1 - 0 - 1 - 3 - 1 - 1 - 1

INTELLIGENT MSIR FLAME DETECTION SYSTEM

■ (Std) FL4000H INTELLIGENT MSIR FLAME DETECTION SYSTEM

A. ALARM-OUTPUT

- 1- ☐ (Std) DUAL MODBUS - 0-20mA, NO RELAYS.....
- 2- ☐ DUAL MODBUS - 0-20mA, RELAYS
- 3- ☐ SINGLE MODBUS - 3.5mA RELAYS, HART
- 4- ☐ SINGLE MODBUS - 1.25mA RELAYS, HART
- 5- ☐ SINGLE MODBUS - 1.25mA NO RELAYS, HART
- 6- ☐ SINGLE MODBUS - 3.5mA NO RELAYS, HART

B. RELAY-STATE-NC:

- 0- ☐ (Std) NO RELAYS.....
- 1- ☐ LATCH ALARM/NON-LATCH WARN DE-ENERGIZED
- 2- ☐ LATCH ALARM/NON-LATCH WARN ENERGIZED
- 3- ☐ LATCH ALARM/LATCH WARN DE-ENERGIZED
- 4- ☐ LATCH ALARM/LATCH WARN ENERGIZED
- 5- ☐ NON-LATCH ALARM/NON-LATCH WARN DE-ENERGIZED
- 6- ☐ NON-LATCH ALARM/NON-LATCH WARN ENERGIZED
- 7- ☐ NON-LATCH ALARM/LATCH WARN DE-ENERGIZED
- 8- ☐ NON-LATCH ALARM/LATCH WARN ENERGIZED

C. SENSITIVITY:

- 1- ☐ (Std) HIGH.....
- 2- ☐ MEDIUM
- 3- ☐ LOW

D. TIME-DELAY:

- 1- ☐ 0 SECOND DELAY
- 2- ☐ 8 SECOND DELAY
- 3- ☐ (Std) 10 SECOND DELAY
- 4- ☐ 14 SECOND DELAY

E. APPROVALS/LANGUAGE:

- 1- ☐ (Std) CSA/FM/ATEX/IECEx
- 3- ☐ CCCF APPROVALS-LED indication for China (GMI)
- 4- ☐ CCCF APPROVALS-LED indication for China (GMIL)

F. WIRING-ARRANGEMENT:

- 1- ☐ (Std) 3/4" NPT CONDUIT ENTRY
- 2- ☐ 2x25mm

G. MOUNTING BRACKET

- 0- ☐ W/O MOUNTING BRACKET
- 1- ☐ (Std) W/MOUNTING BRACKET