



Temporary anchorage points

One of the most important aspects of a fall protection system, is the selection of a reliable anchorage point (A) to ensure full safety. This shall:

- have a static resistance.
- be located at a safe distance above any lower obstacles.
- be as vertical as possible to the work station to avoid the swing effect.

WEBBING ANCHORAGE SLING



Allows a reliable connection point which adapts to a wide range of anchorage points.

FEATURES & BENEFITS

Benefits:

- Easy to install.
- Lightweight.
- Reliable.
- High breaking strength.
- Sheathed end of sling to resist abrasion from connector.

Ref.	Length
10 029 16	0.6m
10 029 17	0.8m

Conforms to EN795b

Features:

- 23mm yellow polyester webbing.
- Breaking strength: > 10kN.
- Colour coded to differentiate lengths.
- Conforms to EN795B:1996.

Ref.	Length
10 032 45	1.0m
10 029 18	1.2m
10 029 19	1.5m



Temporary anchorage points

TITAN™



Webbing anchorage sling.

FEATURES & BENEFITS

Benefits:

- High breaking strength.
- Lightweight.
- Safe and easy-to-install anchorage point.

Features:

- 20mm red and black polyamide webbing.
- Breaking strength: > 10kN.



Ref.	Length
10 083 60	0.6m
10 083 61	0.8m

Conforms to EN795b & EN566

Ref.	Length
10 083 62	1.0m
10 083 63	1.2m
10 083 64	1.5m

MJ51 STEEL SLING



FEATURES & BENEFITS

Benefits:

- Easy-to-install.
- Large opening for anchorage to girders, beams.
- High breaking strength.

Features:

- 6.3mm galvanised steel with protective plastic sheath.
- Breaking strength: >15kN.



Ref.	Length
10 178 22	0.66m
10 028 97	1m
10 031 78	2m
10 031 79	3m

Conforms to EN 795b

WEBBING MOBILE LIFELINE WITH ANCHORAGE SLING



Temporary webbing horizontal lifeline.

FEATURES & BENEFITS

Benefits:

- Offers a large working area.
- Fast and easy to install.
- For use by one or 2 workers.
- Maximum working length 20 metres.
- Fixing to either permanent anchorage points or temporary webbing anchorage slings.

Features:

- Durable polyester webbing with 35 mm.
- Length adjuster.
- Delivered in a bag.

Ref.	Size
10 111 60	20m

Conforms to EN795b

