



FALCON™ EDGE

Edge-tested self retracting lifeline with optimal safety for all situations when working at height

FEATURES & BENEFITS

Benefits:

- Protects in all work situations (horizontal, vertical, mounted overhead, anchored at foot level and work near edges).
- Quick arrest and short fall distance (fall distance <1,40 m, tested at 136 kg).
- Available in 6,2 m, 9 m working lengths; 15 m and 18 m will be available in 2018.
- Increased durability, simple maintenance and extended service.
- Increased lifetime and lower cost of ownership:
 - Quick and easy to maintain (no annual maintenance).
 - After 10 years of use: only cable and shock absorber replacement.

Features:

- Designed for edge applications with an edge radius of $\geq 0,5$ mm.
- Meets the most stringent safety standards, including EN360 Type B, VG11 (Rev 08).
- Certified to 2014 latest test requirements (VG11 edge-tested): Edge configuration tested to max weight - 136 kg.
- Integral shock absorber connected to the worker to increase safety.
- Unique patented shock absorber pack offering longer lifetime versus textile, resistant to UV and humidity (IP67), requires no annual inspection.
- Highly visible fall indicator on ergonomically designed robust handle.
- Corrosion-resistant internal components
- Dual swivels increase mobility and minimize lifeline from twisting.



REF.	CABLE LENGTH (M)	CABLE	CONNECTORS			WEIGHT (KG)	DIMENSIONS MM
			TOP		BOTTOM		
			KARABINER	SWIVEL	SNAP HOOK WITH FALL INDICATOR		
1034053	9	Galvanised steel	•	•	Galvanised steel	4.8	870 x 213 x 101
1034054	15	Galvanised steel	•	•	Galvanised steel	7.5	960 x 246 x 101
1034057	9	Stainless steel	•	•	Stainless steel	4.8	870 x 213 x 101
1034058	15	Stainless steel	•	•	Stainless steel	7.5	960 x 246 x 101

Conforms to EN360 Type B, VG11 (Rev 08)

The CE standard requires inspection by a trained competent person, following the Miller Repair Guide.